Restriction of Hazardous Substances (RoHS)

Environmental Compliance

By Brian Baisden



- This year consumer electronic discards will reach over 300 Million units per year!
- The USA discards 30 million computers each year!
- Mobile phones alone are projected to be discarded at the rate of 100 million per year creating in excess of 65,000 tons of waste.

































RoHS (2002/95/EC) Directive

July 1, 2006, electrical and electronic equipment "put on the market" may not contain Lead, Mercury, Cadmium, Hexavalent Chromium. Polybrominated Biphenyls (PBBs) and Polybrominated Diphenyl Ethers (PBDEs) in amounts exceeding the set Maximum Concentration Values.

.

RoHS Material Limits


- Lead (Pb)
- Mercury (Hg)
- Hexavalent Chromium (CrVI)
- Polybrominated Biphenyls (PBB) or (C₁₂H₄Br₆)
- Polybrominated Diphenyl Ethers (PBDE) 0.1wt% per (1000ppm) "homogeneous material"
- Cadmium (Cd)
 0.01wt% per (100ppm) "homogeneous material"

Lead (Pb)

Printed Wiring Boards

Solder

Cable insulation, Jacketing, Color concentrates



Mercury (Hg)

Switches

Relays

Mercury Discharge Lamps



Hexavalent Chromium (CrVI)

Paints

Toners

Corrosion Inhibitor







Pacific Gas and Electric Hinkley, California

- Polybrominated Biphenyls (PBBs)
- Polybrominated Diphenyl Ethers (PBDEs)

Plastic Connectors and Housings

Cables

Capacitors








Cadmium (Cd)

Cables

Semiconductors

Batteries








Complying with RoHS is Required

Failure to comply with the requirements of RoHS Regulations will result in the removal of the manufacturers products from the market place.

RoHS Decision Tree





Due Diligence

A person shall not be entitled to rely on the defense provided by reason of his reliance on information supplied by another, unless he shows that it was reasonable in all the circumstances for him to have relied on the information.

м

Demonstration of Due Diligence

Product Category

- Review products and accessories to determine RoHS Category
- ☐ Gray products may require 3rd party support
- Document data used to determine category

Exemption review

- Materials and their applications
- Document applicable exemptions

Material data and validation

- Components
- □ Bare board
- Sub assemblies
- Housings
- Plastics
- Sheet metal
- Fasteners



Demonstration of Due Diligence


Quality Management System

- □ Review all Business and Technical Procedures that may cause a RoHS Non-Compliance.
- Modify procedures as necessary.

RoHS Compliance Auditing


- Develop a documented RoHS compliant auditing process.
- □ Validate the effectiveness of modified procedures and processes
- □ Internal Audit results
- □ 3rd Party auditing
- Auditing must be an ongoing activity not a one time event.

Incoming Material Flowchart




(CAR) = Corrective Action Report (NMR) = Non-Conforming Material Report

Vendor Qualification Flowchart.



3RD Party Qualification required if compliance Information can not be obtained.

Corrective Action Flowchart



(CAR) = Corrective Action Report



A producer shall, at the request of the EU enforcement authority, submit within 28 days of the date of the request, technical documents or other information showing that electrical and electronic equipment placed on the market complies with the requirements of the regulations.









Due Diligence, simply means that you have systems and procedures in place that work and that you can prove it.

Tools of Enforcement

X-Ray Fluorescence Analyzer



Notification of concern from external parties


Product Knowledge

- Market intelligence
- Products known to contain materials of high concern
- •High-volume products
- Consumer products unlikely to be recycled



Documentation Review

Challenge to Industry



One product may contain over hundreds of homogeneous materials.




Homogeneous Material

 A Material that cannot be mechanically disjointed into different materials




Mechanically Disjointed

□ The materials can be, in principle, separated by mechanical actions such as unscrewing, cutting, crushing, grinding.



Material in actual cases?

Transmitter Assembly



Investigate Complete System





iDrive Pro TorqueMaster



Remote Transmitter



Remote Entrypad



WallStation Transmitter



Exemptions to the RoHS Directive

Medical Equipment and Control Instruments.

Automotive, Defense and Aerospace Industry Equipment.

See Directive for complete listing of exemptions.

Can your company afford to be shut out of any major market?



HARDWARE

Design and Manufacturing

- Component Identification
- Component Selection
- PCB designs from the perspective of electing solderable coatings.

Immersion Gold

Immersion Silver

Immersion Tin

OSP (Organic Solder Preservative)

м

Design and Manufacturing

Higher heat profiles

Laminates
Number of thermal cycles

 Compatibility of those components to the new thermal profiles.

Bake cycles and double sided mounting on assemblies

Reflow processes


Higher temperatures and longer dwell times

Component Identification

- RoHS does not specify any labeling requirements.
- Industry driven labeling for identification.
- The RoHS label does include all banned materials rather than concentrating on just lead.



Component Identification



м

Laminates

- Must have lead free solderable coatings.
- Must comply with list of identified RoHS materials.
- Must be able to meet new thermal excursion temperatures.
- 5X Thermal shock at 260°C results are a key indicator of material performance in higher temperature lead free assembly applications.

Manufacturing process changes

- Lead free components will require:
 - Training of material handling personnel.
 - Identification of parts and Inspection.
 - □ Providing proper storage and environments.
 - Awareness of moisture sensitivity of components. (MSL)

Moisture Sensitivity Level (MSL)

	Floor Life	
Level	Time	Cond degC/%RH
1	unlimited	<=30/85%
2	1 year	<=30/60%
2a	4 weeks	<=30/60%
3	168 hours	<=30/60%
4	72 hours	<=30/60%
5	48 hours	<=30/60%
5a	24 hours	<=30/60%
6	TOL	<=30/60%


¹⁾ TOL means 'Time on Label', or the time indicated on the label of the packing.

Component Issues for Reliable Pb-Free Assembly

Moisture/Reflow Sensitivity Effect of Peak Reflow Temperature


SolderabilityBackward & Forward Compatibility


Moisture/Reflow Sensitivity



Plastic packages absorb moisture from humidity in the air.

Reflow of Surface Mount Plastic Package







High temperature solder reflow causes condensed internal moisture to vaporize & delaminate weak interfaces.


If internal vapor pressure exceeds strength of plastic, a crack can form.


"Popcorn Effect" Type I Crack






"Popcorn Effect" Type II Crack





Bond Wire Damage



Moisture/Reflow Results

	Peak Reflow Temperature		
MSL	225°C	250°C	260°C
2a	Pass (9 units)	Fail (9/9 popcorn)	Fail (9/9 popcorn)
3		Pass (9 units)	Fail (2/9 small areas of substrate delam.)
4			Pass (9 units)

General Rule-of-Thumb: a 15-20 °C change in peak temperature, will affect moisture sensitivity by one MSL Level.


Lead Free Process Compatibility

Components



No Lead (no Ph) Components





Solder Method



No Lead (no Ph I Solder

250~260 deg C



230~240 deg C

м

Solderability

Pb-free solders will require longer wetting times and higher reflow temperatures.

Recommended times above 235°C >30 sec.

- Peak reflow temperatures > 240°C needed.
- Temperatures must be less than 260°C due to max temp limitations for both components & PWBs.



Life Cycle Testing

Based on complexity of design, further testing may prove valuable to avoid product failures.

- HALT (Highly Accelerated Life Testing)
 - -Identifying the weak points in a design
- HASS (Highly Accelerated Stress Screening)
 - -Designed to only fail production units that have incipient flaws

w

Summary

- RoHS Requires new understanding of product materials & compliance risks.
- RoHS will drive expanded compliance requirements through supply chain.
- Compliance Tools: Education/Testing/Auditing
 Screening products during development can be beneficial.

Special Thanks To:





Quality, Safety and Compliance Experts

Providing Solutions to Improve Product Success in the Marketplace









Reference

- http://www.rohs.gov.uk
- http://www.strquality.com
- http://www.rohsguide.com
- http://ec.europa.eu/environment/waste/weee/index_en.htm
- http://www.pcbnet.com
- http://www.stielectronicsinc.com
- http://www.ul.com

THANK YOU!